PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2001-146457

(43) Date of publication of application: 29.05.2001

(51)Int.CI.

C04B 28/02

B28C 7/00

E04G 21/02

//(C04B 28/02

C04B 22:08

C04B 24:26)

C04B103:40

C04B111:70

(21)Application number : 11-326795

(71)Applicant : **DENKI KAGAKU KOGYO KK**

(22)Date of filing:

17.11.1999

(72)Inventor: TANAKA HIDEHIRO

TAMAKI TOSHIYUKI

(54) CEMENT ADMIXTURE, CEMENT COMPOSITION AND APPLICATION OF CONCRETE USING THE SAME

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a concrete application process that can satisfactorily apply concrete mixtures without leakage from the gaps between mold frames and from crackings, can form the hardened products of stabilized quality without occurrence of phase separation of the material components, causes no loosening and releasing, even when the concrete is applied to the walls, the ceiling face, natural ground and the cavity on the back face of a tunnel.

SOLUTION: The objective cement admixture comprises a water-absorbing polymer that can absorb the water in an amount of $\geq 1,000$ -fold self-weight of the polymer and an alkali metal aluminate as active ingredients. The water- absorbing polymer that can absorb the water in an amount of $\geq 1,000$ -fold self-weight of the polymer and an alkali metal aluminate are separately transferred and admixed to the concrete material and the mixed material is applied to the site.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]